

Einböck

When hoeing
is joy!

DATA SHEET HOEING TECHNOLOGY



WWW.EINBOECK.EU

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Upper link steering	Camera steering system ROW-GUARD	Mechanical feeler for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including row indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
CHOPSTAR 1-30 up to 1 tine up to 30 cm row spacing	12	320	320	700	II/28	20-30	25	40/30	✓	●	-	●	●	●	✓	-	-	-	-
	16	300	420	1200	II/28	20-30	25	70/51	✓	●	-	●	●	●	-	✓	-	-	-
	24	300	620	1560	II/28	20-30	25	80/59	✓	●	-	●	●	●	-	✓	-	-	-
	32	330	820	2120	II/28	20-30	25	90/66	-	●	-	-	-	●	-	✓	-	-	-
	X	C	C	C	C	20-30	C	C	C	C	-	C	C	C	C	C	C	C	C
CHOPSTAR 3-60 up to 3 tines up to 60 cm row spacing	3	160	160	385	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	4	200	200	450	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	5	245	245	515	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	6	300	300	580	II/28	≤ 60	45	40/30	✓	●	●	●	●	●	✓	-	-	-	-
	7	300	335	780	II/28	≤ 60	45	50/37	✓	●	●	●	●	●	✓	-	-	-	-
	8	300	380	880	II/28	≤ 60	45	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	12	300	560	1210	II/28	≤ 60	45	70/51	✓	●	●	●	●	●	-	✓	-	-	-
	15	320	695	1570	II/28	≤ 60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18	480	830	1870	III/36	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2060	II/28	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	✓	-	-
	24	670	1100	2360	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2570	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	≤ 60	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR 5-90 up to 5 tines up to 90 cm row spacing	2	160	160	430	II/28	≤ 90	70	20/15	✓	●	●	●	●	●	✓	-	-	-	-
	4	300	300	560	II/28	≤ 90	70	40/30	✓	●	●	●	●	●	✓	-	-	-	-
		300	300	840	II/28	≤ 90	70	50/37	✓	●	●	●	●	●	-	✓	-	-	-
	6	440	440	820	II/28	≤ 90	70	60/44	✓	●	●	●	●	●	✓	-	-	-	-
		300	440	1010	II/28	≤ 90	70	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	7	320	510	1090	II/28	≤ 90	70	70/51	✓	●	●	●	●	●	-	✓	-	-	-
	8	580	580	990	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1170	II/28	≤ 90	70	80/59	✓	●	●	●	●	●	-	✓	-	-	-
	12	480	860	1810	III/36	≤ 90	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2040	II/28	≤ 90	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16	690	1140	2250	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2500	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	≤ 90	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR 10-150 up to 10 tines up to 150 cm row spacing	2	300	255	480	II/28	≤ 150	150	40/30	✓	●	●	●	●	●	✓	-	-	-	-
	3	300	405	1000	II/28	≤ 150	150	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	X	C	C	C	C	19-30	C	C	C	C	C	C	C	C	C	C	C	C	C

✓ = standard equipment

● = optionally available

- = not possible

Conversion cm in inch = cm / 2,54

Conversion cm in feet = cm / 30,48

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

	PROTECTIVE ELEMENTS					WORKING TOOLS												ACCESSORIES					
	Discs		Rotary hoe star	Shields	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-ST1 JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	Smooth	Serrated																					
	●	-	-	●	✓	13	13	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	17	17	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	25	25	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	33	33	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	C	-	-	C	C	C	C	-	-	-	-	C	-	-	C	-	-	-	C	C	C	C	C
	●	●	-	●	✓	10	4	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	13	5	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	16	6	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	19	7	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	22	8	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	25	9	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	37	13	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	46	16	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	-	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	-	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	-	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	-	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	C	C	-	C	C	C	C	-	C	-	-	C	-	C	C	-	C	C	C	C	C	C	C
	-	●	●	●	✓	11	3	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	21	5	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	21	5	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	31	7	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	31	7	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	36	8	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	41	9	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	-
	-	●	●	●	✓	41	9	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	61	13	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	-
	-	●	●	●	✓	61	13	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	-
	-	●	●	●	✓	81	17	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	-
	-	●	●	●	✓	81	17	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	-
	-	C	C	C	C	C	C	-	C	-	-	C	C	C	C	-	C	C	C	C	C	C	C
	-	●	-	●	✓	20	4	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	-	●	✓	30	6	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	C	-	C	C	C	C	-	C	-	-	C	C	C	C	-	C	C	C	C	C	C	C

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).

Technical changes and mistakes are subject to change without prior notice!

In order to introduce the benefits of our continuous prouct development, we reserve the right to make technical changes without prior notice. Printing and typesetting errors or changes of any kind do not entitle the customer to any claims. Individual equipment specifications, which are illustrated or described here, are only available as options.

In case of contradictions between individual documents regarding the scope of supply, the information in our current price list shall apply.

All pictures are symbol pictures and may contain options which are available for an additional charge. For further information please contact our sales team.

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | Text & Content: © Einböck GmbH; can be used unchanged if source is cited | Version: 10/2024

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Upper link steering	Camera steering system ROW-GUARD	Mechanical feeler for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including row indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
CHOPSTAR-TWIN up to 4 tines 2 cutting discs 35-75 cm row spacing	5	230	200	580	II/28	35-75	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6	275	245	610	II/28	35-75	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	8	300	335	940	II/28	35-75	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12	300	515	1330	II/28	35-75	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15	320	650	1730	II/28	35-75	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18	480	785	2070	III/36	35-75	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		305	785	2260	II/28	35-75	45	130/96	-	●	●	-	-	-	-	-	✓	-	-
	24	670	1055	2650	III/36	35-75	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1055	2860	III/36	35-75	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	II/28	35-75	C	C	C	C	C	C	C	-	C	C	C	C	C
CHOPSTAR-VERSO 3-60 up to 3 tines 2 cutting discs 45-60 cm row spacing	3	160	160	425	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4	200	200	500	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	5	245	245	575	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6	300	300	650	II/28	45-60	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	7	300	335	905	II/28	45-60	45	50/30	✓	●	●	●	●	-	-	✓	-	-	-
	8	300	380	980	II/28	45-60	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12	315	560	1360	II/28	45-60	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15	320	695	1750	II/28	45-60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18	480	830	2090	III/36	45-60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2280	II/28	45-60	45	130/96	-	●	●	-	-	-	-	-	✓	-	-
	24	670	1100	2650	III/36	45-60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2860	III/36	45-60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	45-60	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR-VERSO 5-80 up to 5 tines 2 cutting discs 45-80 cm row spacing	2	160	160	455	II/28	60-80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4	300	300	610	II/28	60-80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	890	II/28	60-80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6	440	440	890	II/28	60-80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1080	II/28	60-80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	7	300	510	1170	II/28	60-80	70	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	8	580	580	1090	II/28	60-80	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1270	II/28	60-80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12	480	860	1950	III/36	60-80	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2180	II/28	60-80	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16	690	1140	2440	III/36	60-80	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2690	III/36	60-80	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	60-80	C	C	C	C	C	C	C	C	C	C	C	C	C

✓ = standard equipment

● = optionally available

- = not possible

Conversion cm in inch = cm / 2,54

Conversion cm in feet = cm / 30,48

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

	PROTECTIVE ELEMENTS					WORKING TOOLS												ACCESSORIES					
	Discs		Rotary hoe star	Shields	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-STI JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	-	-	-	-	✓	10	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	12	6	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	16	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	24	12	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	30	15	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	18	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	18	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	48	24	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	48	24	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	-
	-	-	-	-	✓	10	4	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	13	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	16	6	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	19	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	22	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	25	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	37	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	46	16	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	55	19	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	55	19	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	73	25	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	73	25	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	C
	-	-	-	-	✓	11	3	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	21	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	21	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	31	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	31	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	41	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	41	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	61	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	61	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	81	17	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	81	17	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	C

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).

Technical changes and mistakes are subject to change without prior notice!

In order to introduce the benefits of our continuous prouct development, we reserve the right to make technical changes without prior notice. Printing and typesetting errors or changes of any kind do not entitle the customer to any claims. Individual equipment specifications, which are illustrated or described here, are only available as options.

In case of contradictions between individual documents regarding the scope of supply, the information in our current price list shall apply.

All pictures are symbol pictures and may contain options which are available for an additional charge. For further information please contact our sales team.

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | Text & Content: © Einböck GmbH; can be used unchanged if source is cited | Version: 10/2024

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Upper link steering	Camera steering system ROW-GUARD	Mechanical feeler for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including row indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
CHOPSTAR-PRIME 3-60 up to 3 tines 35-90 cm row spacing	3	160	160	423	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4	200	200	514	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	5	245	245	591	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6	300	300	670	II/28	≤ 60	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	7	300	335	881	II/28	≤ 60	45	50/37	✓	●	●	●	●	-	✓	-	-	-	-
	8	300	380	990	II/28	≤ 60	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12	300	560	1370	II/28	≤ 60	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15	320	695	1770	II/28	≤ 60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18	480	830	2110	III/36	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2300	II/28	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	✓	-	-
	24	670	1100	2670	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2880	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	≤ 60	C	C	C	C	C	C	C	-	C	C	C	C	C
CHOPSTAR-PRIME 5-90 up to 5 tines 61-90 cm row spacing	2	160	160	450	II/28	≤ 90	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4	300	300	575	II/28	≤ 90	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	870	II/28	≤ 90	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6	440	440	870	II/28	≤ 90	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1060	II/28	≤ 90	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	7	300	510	1140	II/28	≤ 90	70	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	8	580	580	1050	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1230	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12	480	860	1900	III/36	≤ 90	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2130	II/28	≤ 90	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16	690	1140	2370	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2620	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	≤ 90	C	C	C	C	C	C	C	-	C	C	C	C	C

✓ = standard equipment

● = optionally available

- = not possible

Conversion cm in inch = cm / 2,54

Conversion cm in feet = cm / 30,48

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | **Text & Content:** © Einböck GmbH; can be used unchanged if source is cited | **Version:** 10/2024

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Upper link steering	Camera steering system ROW-GUARD	Mechanical feeler for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including row indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
ROLLSTAR maize version (8 stars / row) up to 80 cm row spacing	2	190	160	550	II/28	> 80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4	330	300	820	II/28	> 80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	1080	II/28	> 80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6	470	440	920	II/28	> 80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1180	II/28	> 80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	8	320	580	1450	II/28	> 80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	X	C	C	C	C	> 80	C	C	✓	C	C	C	C	C	C	C	C	C	C
ROLLSTAR potato version (4 stars / row) up to 80 cm row spacing	2	180	160	520	II/28	> 80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	3	250	230	490	II/28	> 80	70	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4	320	300	750	II/28	> 80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	1010	II/28	> 80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6	470	440	800	II/28	> 80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1060	II/28	> 80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	8	320	580	1450	II/28	> 80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12	320	860	2000	II/28	> 80	70	140/103	-	●	●	●	●	-	-	-	✓	-	-
	X	C	C	C	C	> 80	C	C	C	C	C	C	C	C	C	C	C	C	C
HILLSTAR up to 80 cm row spacing	2	165	160	360	II/28	65-80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4	300	300	600	II/28	65-80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		280	300	720	II/28	65-80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6	440	440	850	II/28	65-80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	980	II/28	65-80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	8	580	580	1040	II/28	65-80	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1350	II/28	65-80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12	480	860	1580	II/28	65-80	70	120/88	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2100	II/28	65-80	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	X	C	C	C	C	65-80	C	C	C	C	C	C	C	C	C	C	C	C	C

✓ = standard equipment

● = optionally available

- = not possible

Conversion cm in inch = cm / 2,54

Conversion cm in feet = cm / 30,48

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

	PROTECTIVE ELEMENTS					WORKING TOOLS													ACCESSORIES				
	Discs		Rotary hoe star	Shields	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-ST1 JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	Smooth	Serrated																					
	-	●	-	●	✓	4	3	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	8	5	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	8	5	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	12	7	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	12	7	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	16	9	-	-	-	64	-	-	-	-	●	●	●	●	●	●	●	-
	-	C	-	C	C	C	C	-	-	-	C	-	-	-	-	C	C	C	C	C	C	C	C
	-	-	-	●	✓	3	3	-	-	-	8	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	4	4	-	-	-	12	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	5	5	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	5	5	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	7	7	-	-	-	24	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	7	7	-	-	-	24	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	9	9	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	13	13	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	C	C	C	C	-	-	-	-	-	-	-	-	C	C	C	C	C	C	C	C
	-	-	-	-	✓	3	3	-	-	-	-	-	-	4	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	5	5	-	-	-	-	-	-	8	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	5	5	-	-	-	-	-	-	8	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	7	7	-	-	-	-	-	-	12	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	7	7	-	-	-	-	-	-	12	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	9	9	-	-	-	-	-	-	16	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	9	9	-	-	-	-	-	-	16	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	13	13	-	-	-	-	-	-	24	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	13	13	-	-	-	-	-	-	24	-	●	-	-	●	●	●	●	-
	-	-	-	-	C	C	C	-	-	-	-	-	-	-	-	C	-	-	C	C	C	C	C

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).

Technical changes and mistakes are subject to change without prior notice!

In order to introduce the benefits of our continuous prouct development, we reserve the right to make technical changes without prior notice. Printing and typesetting errors or changes of any kind do not entitle the customer to any claims. Individual equipment specifications, which are illustrated or described here, are only available as options.

In case of contradictions between individual documents regarding the scope of supply, the information in our current price list shall apply.

All pictures are symbol pictures and may contain options which are available for an additional charge. For further information please contact our sales team.

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | Text & Content: © Einböck GmbH; can be used unchanged if source is cited | Version: 10/2024