

Einböck

When hoeing
is joy!

DATA SHEET CAMERA STEERING SYSTEM ROW-GUARD



WWW.EINBOECK.EU

Type	Weight approx. kg / lbs	for frame	Hoe kg / lbs	Mounting category		1 single acting hydraulic valve with permanent oil-flow and pressure- free return line
				front	back	
ROW-GUARD 500	390	< 6.99 m / 22.90 ft	≤ 2500 / 5511	II/28	II/28	1
ROW-GUARD 500 SR	530	< 12.2 m / 40.00 ft	≤ 3900 / 8598	III/36	III/36	1
ROW-GUARD 500 SRHD	960	> 12.2 m / 40.00 ft	> 4000 / 8818	III/36	III/36	1

✓ = standard equipment

● = optionally available

– = not possible

Conversion cm in inch = cm / 2,54
Conversion cm in feet = cm / 30,48

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

Technical changes and mistakes are subject to change without prior notice!

In order to introduce the benefits of our continuous prouct development, we reserve the right to make technical changes without prior notice. Printing and typesetting errors or changes of any kind do not entitle the customer to any claims. Individual equipment specifications, which are illustrated or described here, are only available as options.

In case of contradictions between individual documents regarding the scope of supply, the information in our current price list shall apply.

All pictures are symbol pictures and may contain options which are available for an additional charge. For further information please contact our sales team.

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | Text & Content: © Einböck GmbH; can be used unchanged if source is cited | Version: 04/2024